

connecting module N (01 364)



Description

Article

Part No.: 01 364

CRITO[®] 30Compact
connecting module N
10 - 120 mm²
for busbars 12 x 5, 10

System

30Compact 5P

Product group 07

Subgroup 44

pack size 1

EAN 4021267013646

Catalog page 2015 : 1/5

eCl@ss 6.1 27141146
eCl@ss 7.1 27141146
ETIM 4.0 EC000001
ETIM 5.0 EC000001

Approvals

Standards

IEC 61439-1:2011
IEC 60999-1:1999
IEC 60999-2:2003

CCC approval: no certification required

Product data

Electrical data

Rated voltage (IEC) AC: 690
V

rated peak withstand current I_{pk} : 35.1 kA
rated short-time withstand current I_{CW} : 3,5 kA / 1s

Mechanical data

W x H x D: 30 x 160 x 80
Weight: 21.5 kg/100
for busbars: 12 x 5, 10

Terminal points

35 - 120 mm² / AWG 6 - MCM 250
flexible cables, directly or with wire-end ferrule,
stranded round cables,
la. Cu 12x4 - 15,5x10

(flexible cables of maximum cross-section may not fit when using wire-end ferrule)

Material properties

Main body: temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 200

Cover: temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 200